

Declaration of Performance

No. CZ0002-23 (eng)

1 Unique identification code of the product-type

108 03

Product/s:

ISOVER FireProtect® 150
(ISOVER Tank Roof Slab 20 kPa)
ISOVER FireProtect® 150 F

2 Intended use or uses:

Thermal Insulation of Building Equipment and Industrial Installations (ThIBEII)

3 Manufacturer:

Saint - Gobain Construction Product CZ a.s.
Smrčková 2485/4, 180 00 Prague 8 - Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative:

not relevant

5 Systém/s of AVCP:

System 1
System 3

6 Notified body/ies:

1023

Institut pro testování a certifikaci a.s.

Harmonised standard:

EN 14303:2009+A1:2013

Essential characteristics	Performance						Abbreviation		Unit		Declared performance/s:	
Reaction to fire	Reaction to fire						RtF		Euroclass		A1	
Acoustic absorption index	Sound absorption						-		-		NPD	
Thermal resistance	Thermal conductivity	T °C	10 °C	50 °C	100 °C	200 °C	300 °C	400 °C	500 °C	600 °C	700 °C	
		λ_D (W/m²K)	0,036	0,041	0,047	0,060	0,077	0,098	0,123	0,154	0,192	
	Thickness						d		mm		20-100	
	Tolerances						T				T5	
Water permeability	Water absorption						WS		kg/m²		WS1	
Water vapour transmission	Water vapour diffusion resistance						s _d		m		NPD	
Compressive strength	Compressive stress or compressive strength for flat products						CS		kPa		20	
Rate of release of corrosive substances	Trace amounts of soluble ions and pH value						CL		mg/kg		10	
	Realease of Dangerous Substances						-		-		NPD	
Continous glowing combustion	Continous glowing combustion						-		-		NPD	
Durability of against reaction to fire ageing/degradation	Durability Characteristics						RtF		Euroclass		A1	
Durability of reaction to fire against ageing/degradation and against high temperature	Durability Characteristics						-		-		NPD	
Durability of thermal resistance against ageing/degradation and against high temperature	Maximum Service Temperature						ST(+)		°C		700	
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensions and tolerances						T		-		T5	
	Dimensional stability, or						DS(TH)		-		NPD	
	Maximum Service Temperature						ST(+)		°C		700	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name
Plant director
Function


Signature

1.9.2023
Date
Častolovice
Place


e-mail: info@isover.cz
www.isover.cz