## **Declaration of Performance**

No. CZ0002-008 (eng)

Unique identification code of the product-type

103 02

Product/s:

## **Orstech LSP 40**

**TECH Lamella Mat MT 2.1 Alu2** 

Intended use or uses:

Thermal insulation of Building Equipment and Industrial Installations (ThIBEII)

Manufacturer:

Saint - Gobain Construction Product CZ a.s. Smrčkova 2485/4, 180 00 Prague 8 - Libeň **Czech Republic** 

IČO: 25029673, DIČ: CZ 25029673

**Authorised representative:** 

not relevant System 1

System 3

Systém/s of AVCP:

Institut pro testování a certifikaci a.s.

Harmonised standard:

Notified body/ies:

EN 14303:2009 + A1:2013

Declared

Essential characteristics	Performance	Abrevi	Abreviation		Unit		performance/s:	
Reaction to fire	Reaction to fire	Rt	RtF		Euroclass		A2-s1,d0	
Acoustic absorption index	Sound absorption	-	-		-		NPD	
Thermal resistance	Thermal resistance	T °C	50 ° C	100 ° C	150 ° C	200 ° C	250 ° C	
		$^{\lambda_{D}}$ (W/m*K)	0.046	0.056	0.069	0.084	0.103	
	Thickness	-	d		mm		20-100	
	Tolerances	·	Т			T	T4	
Water permeability	Water absorption	W	WS		kg/m2		WS1	
Water vapour transmission	Water vapour diffusion resistance	Sı	S <sub>d</sub>		m		NPD	
Rate of release of corrosive substances	Trace amounts of soluble ions and pH value	Ci	CL		mg/kg		10	
	Realease of Dangerous Substances	-	-		-		NPD	
Continous glowing combustion	Continous glowing combustion	-	-		-		NPD	
Durability of against reaction to fire ageing/degradation	Durability Characteristics	Rt	RtF		Euroclass		A2-s1,d0	
Durability of reaction to fire against ageing/degradation and against high temperature	Durability Characteristics	-	-		-		NPD	
Durability of thermal resistance against ageing/degradation and against high temperature	Maximum Service Temperature	ST(	ST(+)		°C		250	
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensions and tolerances	Т	Т		-		T4	
	Dimensional stability, or	DS(	DS(TH)		-		NPD	
	Maximum Service Temperature	ST(	ST(+)		°C		250	

1023

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák Name Plant director Function



1.9.2023 Date Častolovice Place

