

Declaration of Performance

No. CZ0002-004 (eng)

1 Unique identification code of the product-type

103 03

Product/s:

Orstech LSP H

TECH Lamella Mat MT 2.2 Alu2

2 Intended use or uses:

Thermal Insulation of Building Equipment and Industrial Installations (THIBEI)

3 Manufacturer:

Saint - Gobain Construction Product CZ a.s.
Smrčkova 2485/4, 180 00 Prague 8 - Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative:

not relevant

5 Systém/s of AVCP:

System 1
System 3

6 Notified body/ies:

1023

Institut pro testování a certifikaci a.s.

Harmonised standard:

EN 14303:2009 + A1:2013

| Essential characteristics | Performance | Abbreviation | Unit | Declared performance/s: | | | | | | |
|--|--|------------------------|-------------------|-------------------------|--------|--------|--------|--------|--------|--------|
| Reaction to fire | Reaction to fire | RtF | Euroclass | A2-s1,d0 | | | | | | |
| Acoustic absorption index | Sound absorption | - | - | NPD | | | | | | |
| Thermal resistance | Thermal resistance | T °C | 50 °C | 100 °C | 150 °C | 200 °C | 300 °C | 400 °C | 500 °C | 600 °C |
| | | λ_D (W/m*K) | 0,046 | 0,056 | 0,069 | 0,084 | 0,125 | 0,180 | 0,251 | 0,340 |
| | Thickness | d | | mm | | 20-100 | | | | |
| | Tolerances | T | | - | | T4 | | | | |
| Water permeability | Water absorption | WS | kg/m ² | WS1 | | | | | | |
| Water vapour transmission | Water vapour diffusion resistance | s _d | m | NPD | | | | | | |
| Rate of release of corrosive substances | Trace amounts of soluble ions and pH value | CL | mg/kg | 10 | | | | | | |
| | Realease of Dangerous Substances | - | - | NPD | | | | | | |
| Continous glowing combustion | Continous glowing combustion | - | - | NPD | | | | | | |
| Durability of against reaction to fire ageing/degradation | Durability Characteristics | RtF | Euroclass | A2-s1,d0 | | | | | | |
| Durability of reaction to fire against ageing/degradation and against high temperature | Durability Characteristics | - | - | NPD | | | | | | |
| Durability of thermal resistance against ageing/degradation and against high temperature | Maximum Service Temperature | ST(+) | °C | 600 | | | | | | |
| Durability of thermal resistance against heat, weathering, ageing/degradation | Dimensions and tolerances | T | | - | | T4 | | | | |
| | Dimensional stability, or | DS(TH) | | - | | NPD | | | | |
| | Maximum Service Temperature | ST(+) | | °C | | 600 | | | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name
Plant director
Function


Signature

1.9.2023
Date
Častolovice
Place


SAINT-GOBAIN
e-mail: info@isover.cz
www.isover.cz